

STENI EDGE PAINT WITH ROLLER

Prerequisite: Edge paint with roller can be used as an edge lacquer solution for entire projects where a colored edge is desired. Dark edge lacquer can be ordered pre-applied from the factory.

NB! Follow the manufacturer's recommendations in relation to temperature, primer and preparation. It is recommended that an acrylic paint from a well-known supplier is used. For example Jotun, Beckers, Scanox, Flügger etc.

NB! Remember to read the products' safety data sheets carefully and use the correct personal protective equipment.



1. Preparation:

- Clean the edge surface and remove dirt and grime
- A microfiber cloth or other dust-free cloth can be used
- Dampen the cloth in a solution of about 5% aqua petrosol or common water-based detergent for removing dirt and dust and lukewarm water.
- Then allow the surface to dry

2. Application:

- For best results, the area should be at room temperature. See the recommendation on the paint can.
- Stir the paint well before application
- Use a sponge roller for an especially attractive finish
- Apply in a smooth motion with an angle of about 60° towards the back side to avoid paint spills on the lacquered surface of the Steni plate
- Paint spills on the surface must be removed immediately in one motion
- Allow to dry! The application should not be exposed to moisture for at least 120 minutes (a longer drying time must be expected in colder environments than those indicated on the paint tin)



TIPS!

- Clean well
- Use acrylic-based paint
- Remember to use personal protective equipment
- Small areas can be repaired with oil-based felt-tip pens. For example UNI Paint PX-30
- The NCS code on the Steni plate can be used to obtain the correct paint

